




PCI / RB03 / 05242
10/956663 #2



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.


In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)


Signed *Andrew Gjersey*
Dated 12 January 2004



BEST AVAILABLE COPY

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)



The Patent Office

Cardiff Road
Newport
South Wales
NP9 1RH

1. Your reference	MS/P501162		
2. Patent application number (The Patent Office will fill in this part)	0228006.3		30 NOV 2002
3. Full name, address and postcode of the or of each applicant (underline all surnames)	MARKES INTERNATIONAL LIMITED Unit D3 Llantrisant Business Park Pontyclun, Rhondda Cynon Taff CF72 8YW 74216 54001 UNITED KINGDOM		
Patents ADP number (If you know it)			
If the applicant is a corporate body, give the country/state of its incorporation			
4. Title of the invention	ANALYTICAL APPARATUS		
5. Name of your agent (If you have one)	URQUHART-DYKES & LORD		
"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	Three Trinity Court 21-27 Newport Road CARDIFF CF24 0AA		
Patents ADP number (If you know it)	1644025 ✓		
6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number	Country	Priority application number (if you know it)	Date of filing (day / month / year)
7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application	Number of earlier application		Date of filing (day / month / year)
8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if)	YES		
a) any applicant named in part 3 is not an inventor, or			
b) there is an inventor who is not named as an applicant, or			
c) any named applicant is a corporate body.			
See note (d))			

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 6

Claim(s) -

Abstract -

Drawing(s)

2

10. If you are also filing any of the following, state how many against each item.

Priority documents -

Translations of priority documents -

Statement of inventorship and right to grant of a patent (Patents Form 7/77) -

Request for preliminary examination and search (Patents Form 9/77) -

Request for substantive examination (Patents Form 10/77) -

Any other documents (please specify) -

11.

I/We request the grant of a patent on the basis of this application.

Signature
URQUHART-DYKES & LORD

Date
29 November 2002

12. Name and daytime telephone number of person to contact in the United Kingdom

Dr Mark Spittle (Tel: 029 2048 7993)

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

DUPLICATE

Analytical Apparatus

The present invention relates to an analytical apparatus and, more particularly, to an automatic thermal desorption apparatus.

It is known to provide a thermal desorption apparatus
5 comprising an autosampler for automatically selecting one of a plurality of sampling tubes stored therein, heating the tube to desorb a sample from a sorbent material contained in the tube and then providing a flow of inert gas through the tube to drive the sample therefrom.

10 Known apparatus further comprise means for analysing a first portion of the sample driven from each sampling tube and for collecting a second portion of the sample in a respective collecting tube, for subsequent analysis.

However, a drawback of such known apparatus is that,
15 following the analysis of samples released from a number of sampling tubes, their respective collecting tubes must be manually loaded into the autosampler for a subsequent analysis to be carried out.

A further drawback of such known apparatus is that
20 automatic storage means must be provided for storing the collecting tubes in which respective portions of the samples released from each of the sampling tubes are collected, independent of the autosampler in which the sampling tubes are stored.

25 We have now devised an arrangement which overcomes the limitations of known analytical apparatus.

In accordance with the present invention, there is provided an analytical apparatus comprising means for automatically carrying out the steps of:

30 releasing a sample from a sampling tube;
analysing a first portion of the released sample;
collecting a second portion of the released sample;
re-releasing the collected said second portion of the sample; and

analysing the re-released portion of the sample.

The apparatus may be arranged to select the sampling tube from a plurality of tubes stored in an autosampler. The apparatus thus obviates the requirement for the manual loading
5 of collecting tubes into an autosampler, for a two stage analysis to be carried out on samples contained in a plurality of sampling tubes.

Preferably the apparatus is arranged to provide a comparison of the results from each of the two analysis stages.

10 Preferably, the second portion of the sample released from each sampling tube is collected either in the sampling tube itself or in a separate collecting tube or trap.

In the latter case, preferably either a single collecting tube or trap is used to collect, in turn, the second
15 portion of the sample released from each of a plurality of sampling tubes, or respective collecting tubes are used to collect the second portion of each of the released samples, each of said respective collecting tubes preferably being selected automatically from a plurality of tubes stored either
20 in the same autosampler as the sampling tubes or in a further autosampler.

Preferably, only a portion of the re-released sample is analysed, a second portion of the re-released sample being re-collected, either in the sampling tube or in a further
25 respective re-collecting tube, each of said respective re-collecting tubes preferably being selected automatically from a plurality of tubes stored either in the same autosampler as the sampling tubes and/or collecting tubes or in a further autosampler.

30 The apparatus may be arranged such that the sample released from the sampling tube is buffered, by collecting the sample in an intermediate tube or trap, prior to the steps of analysing the first portion of the released sample and collecting the second portion of the released sample.
35 Alternatively, the second portion of the sample released from

the sampling tube, or subsequently collected and re-released, may be buffered, by collecting the sample in an intermediate tube or trap, prior to its collection/re-collection.

Also in accordance with the present invention, there is provided an analytical apparatus, comprising means for automatically carrying out, for each of a plurality of sampling tubes stored in an autosampler, the steps of:

selecting a sampling tube from said plurality of tubes;
releasing a sample from the sampling tube;
10 analysing a first portion of the released sample;
collecting a second portion of the released sample,
either in the sampling tube or in a collecting tube selected from said plurality of tubes, with which said first tube is replaced in the autosampler.

15 The apparatus thus obviates the requirement for automatic storage means for storing the collecting tubes in which respective portions of the samples released from each of the sampling tubes are collected, independent of the autosampler in which the sampling tubes are stored.

20 The apparatus may also comprise means for automatically carrying out the further steps of releasing the sample collected in either the sampling tube or the collecting tube and analysing the released sample.

The apparatus may be arranged to analyse only a first
25 portion of the sample released by said collecting means, a second portion of the released sample being re-collected, either in the sampling tube, the collecting tube or in a re-collecting tube selected from said plurality of tubes, with which either the sampling tube or the collecting tube is
30 replaced in the autosampler.

The apparatus may be arranged such that, for each of the plurality of sampling tubes, the sample released from the sampling tube is buffered, by collecting the sample in a tube or trap, prior to the steps of analysing the first portion of
35 the released sample and collecting the second portion of the

released sample. Alternatively, the second portion of the sample released from the sampling tube or by the collecting means may be buffered, by collecting the sample in a tube or trap, prior to its collection/re-collection.

5 Embodiments of the present invention will now be described by way of examples only and with reference to the accompanying drawings, of which:

Figure 1 is a schematic illustration of an embodiment of apparatus in accordance with the present invention;

10 Figure 2 to 5 are schematic illustrations of respective modes of operation of the apparatus of Figure 1

Figure 6 and 7 are schematic illustrations of respective modes of operation of a second embodiment of apparatus in accordance with the present invention.

15 Referring to Figure 1, a first embodiment of analytical apparatus in accordance with the present invention is schematically illustrated, the apparatus comprising an autosampler 2, within which a plurality of sorbent tubes are stored (sampling tubes), analysis means 4 and a further sorbent
20 tube (collecting tube) or trap 6. The autosampler may instead be replaced by a single sampling tube.

In a first mode of operation of the apparatus, illustrated in Figures 2 and 3, sampling tubes are automatically selected, in turn, from those stored in the
25 autosampler. Each tube (L) is first heated to desorb a sample from a sorbent material contained therein and the desorbed sample driven from the tube by a flow of inert gas therethrough.

A first portion of the sample driven from the sampling
30 tube (L) is analysed by the analysing means 4 and a second portion passed through the collecting tube (A), within which it is adsorbed by the sorbent material therein or contained in a trap.

The collecting tube (A) is then heated to desorb the
35 sample from the sorbent material therein and is driven out of

the tube by a reversed flow of inert gas.

The entire sample thus released from the collecting tube (A) may then be passed through the sampling tube (L), within which it is re-adsorbed for archiving or subsequent analysis (Figure 2), or only a portion of the sample may be passed through the sampling tube (L) for re-adsorption, with a second portion of the sample being analysed by the analysing means 4 (Figure 3). In the former case the apparatus preferably comprises means for cooling the sampling tube (L) to facilitate re-adsorption by the sorbent material contained therein. In both cases, the apparatus preferably comprises means for cooling the collecting tube (A) to facilitate adsorption by the sorbent material contained therein.

In a first modification of the above process, illustrated schematically in Figures 4 and 5, the whole (Figure 4) or a portion (Figure 5) of the sample released from the collecting (A) tube may be passed through a sorbent tube (M) other than the sampling tube (re-collecting tube), with which the sampling tube (L) is replaced in the autosampler.

The same process may be repeated for each sampling tube (L,N) selected from the autosampler, either using a single collecting tube (A) for collecting the second portion of the sample released from each sampling tube (Figures 4 and 5) or using a respective collecting tube (A,B) for each sample, as illustrated schematically in Figures 6 and 7, with each collecting tube being selected, in turn, from a plurality of collecting tubes stored in a second autosampler. In the former case, the apparatus preferably comprises means for cooling the collecting tube (A) to facilitate adsorption by the sorbent material contained therein.

As a variation on the processes illustrated in Figures 2, 4, and 6, the entire sample driven from each sampling tube may be collected in a collecting tube, a first portion of the sample subsequently released from the collecting tube being analysed by the analysing means 4, with a second portion of the

sample being re-collected in the sampling tube or a re-collection tube. The apparatus preferably comprises means for cooling the collecting tube to facilitate adsorption by the sorbent material contained therein.

5 It would also remain in accordance with the present invention, in those embodiments in respect of which the use of only a single collecting tube has been described, for the collecting tube to be substituted with a trap.

10 The various apparatus thus described provide an efficient and labour saving means for the thermal desorption of a plurality of samples contained in respective sampling tubes, wherein a portion of the desorbed sample is to be collected for subsequent analysis.

CLAIMS

- 1) An analytical apparatus comprising means for automatically carrying out the steps of:
- releasing a sample from a sampling tube;
 - 5 analysing a first portion of the released sample;
 - collecting a second portion of the released sample;
 - re-releasing the collected said second portion of the sample; and
 - analysing the re-released portion of the sample.
- 10 2) An analytical apparatus according to claim 1, which is arranged to select the sampling tube from a plurality of tubes stored in an autosampler.
- 3) An analytical apparatus according to claim 1 or 2, which is arranged to provide a comparison of the results from each of
- 15 the two analysis stages.
- 4) An analytical apparatus according to any preceding claim, wherein the second portion of the sample released from each sampling tube is collected either in the sampling tube itself or in a separate collecting tube or trap.
- 20 5) An analytical apparatus according to claim 4, wherein a single collecting tube or trap is used to collect, in turn, the second portion of the sample released from each of a plurality of sampling tubes.
- 6) An analytical apparatus according to claim 4, wherein
- 25 respective collecting tubes are used to collect the second portion of each of the released samples.

- 7) An analytical apparatus according to claim 6, wherein each of said respective collecting tubes are selected automatically from a plurality of tubes stored either in the same autosampler as the sampling tubes or in a further autosampler.
- 5 8) An analytical apparatus according to any preceding claim, wherein a portion of the re-released sample is analysed, a second portion of the re-released sample being re-collected, either in the sampling tube or in a further respective re-collecting tube, each of said respective re-collecting tubes
10 being selected automatically from a plurality of tubes stored either in the same autosampler as the sampling tubes and/or collecting tubes or in a further autosampler.
- 9) An analytical apparatus according to any preceding claim, arranged such that the sample released from the sampling tube
15 is buffered, by collecting the sample in an intermediate tube or trap, prior to the steps of analysing the first portion of the released sample and collecting the second portion of the released sample.
- 10) An analytical apparatus according to any of claims 1 to
20 8, wherein the second portion of the sample released from the sampling tube, or subsequently collected and re-released, are buffered, by collecting the sample in an intermediate tube or trap, prior to its collection/re-collection.
- 11) An analytical apparatus comprising means for
25 automatically carrying out, for each of a plurality of sampling tubes stored in an autosampler, the steps of:
- selecting a sampling tube from said plurality of tubes;
 - releasing a sample from the sampling tube;
 - analysing a first portion of the released sample;
 - 30 collecting a second portion of the released sample,

either in the sampling tube or in a collecting tube selected from said plurality of tubes, with which said first tube is replaced in the autosampler.

12) An apparatus according to claim 11, which further
5 comprises means for automatically carrying out the further steps of releasing the sample collected in either the sampling tube or the collecting tube and analysing the released sample.

13) An apparatus according to claim 11 or 12, which is
10 arranged to analyse only a first portion of the sample released by said collecting means, a second portion of the released sample being re-collected, either in the sampling tube, the collecting tube or in a re-collecting tube selected from said plurality of tubes, with which either the sampling tube or the collecting tube is replaced in the autosampler.

15 14) An apparatus according to any of claims 11 to 13, wherein for each of the plurality of sampling tubes, the sample released from the sampling tube is buffered, by collecting the sample in a tube or trap, prior to the steps of analysing the first portion of the released sample and collecting the second
20 portion of the released sample.

15) An apparatus according to any of claims 11 to 13, wherein the second portion of the sample released from the sampling tube or by the collecting means may be buffered, by collecting the sample in a tube or trap, prior to its collection/re-
25 collection.

AbstractAnalytical Apparatus

An analytical apparatus comprising means for automatically carrying out the steps of:

- 5 releasing a sample from a sampling tube;
- analysing a first portion of the released sample;
- collecting a second portion of the released sample;
- re-releasing the collected said second portion of the
- sample; and
- 10 analysing the re-released portion of the sample.




Figure 1




Figure 2




Figure 3




Figure 4




Figure 5




Figure 6




Figure 7

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☒ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.